

**PROFESSIONAL SECRETS TO
EFFECTIVE FLOOR CARE**

DIRECTIONS FOR USE:

FIRST REFLECTIONS provides an excellent base for the application of acrylic floor finishes. For best results, apply two coats to provide superior adherence to flooring substrate, as well as leveling a floors surface imperfections to maximize the gloss potential of your floor finish.

Always apply FIRST REFLECTIONS to a newly stripped floor. With a clean, rayon/cotton blend mop, apply by first "framing" the area to be finished, then go back and fill in the "framed" area with a gentle side-to-side mopping motion, being certain to overlap each pass slightly. If a rectangular applicator is used, be certain that each pass slightly overlaps the previous one.

Let each coat dry to the touch before recoating. Drying time is approximately 30 minutes. High humidity could prolong drying time. A fan can be used to reduce drying time. Allow the seal to set for 10 minutes before starting a fan. Do not use a fan in areas where dust could be blown onto sealer. Apply a second coat of FIRST REFLECTIONS using the same method outlined above. After 30 minutes begin applying a floor finish.

FIRST REFLECTIONS

LONG-LASTING
FLOOR SEALER AND UNDERCOAT

SPECIFICALLY FORMULATED TO
ENHANCE THE APPEARANCE OF
RESILIENT FLOORING

SUPERIOR BASE COAT FOR
ACRYLIC FINISHES SUBJECTED TO
EITHER BURNISHING OR
SPRAY BUFFING OPERATIONS

CAUTION

May irritate eyes. Do not take internally.
See side panel for additional precautionary
statements and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

- Do not use your stripping or rinsing mop, or bucket, for the application of floor sealers. Always start with a clean, previously wrung-out cotton/rayon mop and bucket. Save this mop and bucket just for the application of sealer.

- To avoid the accumulations of finish build-up in corners or on baseboards, always apply the first coat no closer than 12 inches from baseboards. Apply second coat, and every other coat up to baseboards.

- Always apply even, medium coats. To ensure the application of medium coats, wring out the bottom half of a fully saturated mop.

- Discard unused sealer. Pouring unused sealer from your bucket back into the original container can spoil the good sealer.


CAUTION

May irritate eyes. Do not take internally. Avoid contact with eyes. Prolonged or repeated contact with skin may cause irritation. Use with adequate ventilation. If in eyes, flush with cool water for at least 15 minutes, if irritation persists, obtain medical assistance. If swallowed, contact physician or poison control center immediately. Do not induce vomiting. If on skin, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN

This product contains:	CAS Number:
Water	7732-18-5
Styrene Acrylic Copolymer	25-35-68-1
Ethanol, 2-(2 methoxyethoxy)	111-77-3
Ethene, homopolymer, oxidized	68441-17-8
Propene, homopolymer, oxidized	68649-58-1

1710.012306



NET CONTENTS:

5 6 20 30 55

GALLONS