

DIRECTIONS FOR USE: LUSTRE RESTORER has been precision formulated to match the composition of CRYSTAL Floor Finish. Its unique Reactive Polymer Matrix (RPM) utilizes the heat produced by Ultra High Speed (UHS) burnishing equipment to create a spectacular, highly reflective “wet look” gloss. A daily burnishing program, featuring LUSTRE RESTORER, repairs scratches and marks, enhances finish durability and extends finish life.

1. Dry mop the entire floor using a dust mop treated with CLEAR ATTRACTIONS Dust Mop Treatment to remove loose soil.
2. Clean floor with a damp mop or an autoscrubber using EXCEL CLEANER following label directions.
3. Dilute 2 to 4 ounces of LUSTRE RESTORER per gallon of warm water.

MOP APPLICATION: Mop on a medium, even coat of LUSTRE RESTORER solution, being certain to cover all areas of floor. Allow to dry to a slight haze (approximately 20 to 30 minutes). Burnish with a white or beige pad using your electric, battery or propane powered UHS machine.

AUTOSCRUBBER APPLICATION: Mix LUSTRE RESTORER in autoscrubber tank (approximately 1/2 gallon into a 14 gallon tank). Scrub with a red pad. Pick up solution with vacuum.

Hazardous Materials Information System (HMIS)				National Fire Protection Association (NFPA)		
HEALTH	1	Severe	4	Extreme	HEALTH	1
FLAMMABILITY	0	Severe	3	High	FLAMMABILITY	0
REACTIVITY	0	Moderate	2	Moderate	REACTIVITY	0
PERSONAL PROTECTION	B	Slight	1	Slight	SPECIAL PRECAUTIONS	0
		Minimal	0	Insignificant		

LUSTRE RESTORER

MOP-ON FLOOR
UHS RESTORER CONCENTRATE

REACTIVE POLYMER MATRIX
RESPONDS TO BURNISHING TO
RECREATE “WET LOOK” SHINE

RENEWS SURFACES
REPAIRS SCRATCHES AND MARKS

CAUTION

May irritate eyes. Do not take internally. See side panel for additional precautionary statements and first aid instructions.
KEEP OUT OF REACH OF CHILDREN

Sold By:

Damp mop to pick-up all puddles. Allow to dry to a slight haze (approximately 5 to 10 minutes). Burnish with a white or beige pad using your electric, battery or propane powered UHS machine.

PROFESSIONAL SECRETS TO EFFECTIVE FLOOR CARE

1. Floors should be dust mopped and damp mopped before spray buffing - accumulated dust and dirt cause unsightly scratches or abrasion that will significantly reduce finish durability and lead to frequent stripping and recoating.
2. Inspect pads frequently. If pads show an accumulation of old floor finish, dirt or accumulated restorer solution in the space between pad fibers, clean or replace immediately.

CAUTION

May irritate eyes. Do not take internally. Avoid contact with eyes. Prolonged or repeated contact with skin may cause irritation. Use with adequate ventilation. If in eyes, flush with cool water for at least 15 minutes, if irritation persists, obtain medical assistance. If swallowed, contact physician or poison control center immediately. Give person several glasses of water and induce vomiting. Never induce vomiting or give anything by mouth to an unconscious person. If on skin, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN

171293005

NET CONTENTS:

5 6 20 30 55
GALLONS