

### SECTION 1: Product and company identification

Product name : Baseboard Stripper  
 Use of the substance/mixture : Aerosol  
 Floor wax stripper  
 Product code : 8177  
 Company : Total Solutions  
 P.O. Box 240014  
 Milwaukee, WI 53224 - USA  
 T (414) 354-6417  
 Emergency number : Chemtec: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)


Compressed gas H280  
 Met. Corr. 1 H290  
 Skin Corr. 1B H314

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Contains gas under pressure; may explode if heated  
 May be corrosive to metals  
 Causes severe skin burns and eye damage

Precautionary statements (GHS-US) :

Keep only in original container  
 Do not breathe mist  
 Wash thoroughly after handling  
 Wear protective gloves, protective clothing, eye protection, face protection  
 If swallowed: rinse mouth. Do NOT induce vomiting  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 If inhaled: Remove person to fresh air and keep comfortable for breathing  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a doctor, a POISON CENTER  
 Specific treatment (see First aid measures on this label)  
 Wash contaminated clothing before reuse  
 Absorb spillage to prevent material damage  
 Store locked up  
 Store in corrosive resistant container with a resistant inner liner  
 Protect from sunlight. Store in a well-ventilated place  
 Dispose of contents/container to comply with local/regional/national/international regulations

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
butane	(CAS No) 106-97-8	5 - 10	Flam. Gas 1, H220 Compressed gas, H280

# Baseboard Stripper

## Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
Glycol Ether EB	(CAS No) 111-76-2	1 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT RE 2, H373 Asp. Tox. 1, H304
2-aminoethanol, ethanolamine	(CAS No) 141-43-5	1 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 STOT SE 3, H335
propane	(CAS No) 74-98-6	1 - 5	Flam. Gas 1, H220 Compressed gas, H280

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.
- First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May be harmful if swallowed. Causes severe skin burns and eye damage.
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : Harmful if swallowed. Burns to the gastric/intestinal mucosa. Gastrointestinal complaints.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Water fog. Foam.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Under fire conditions closed containers may rupture or explode.
- Explosion hazard : Bursting aerosol containers may be propelled from a fire at high speed. Contains gas under pressure; may explode if heated. Vapors may travel long distances along ground before igniting/flashing back to vapor source.
- Reactivity : Upon combustion: CO and CO<sub>2</sub> are formed.

#### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Evacuate area. No action shall be taken involving any personal risk or without suitable training. Move containers away from the fire area if this can be done without risk. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Isolate from fire, if possible, without unnecessary risk.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Do not enter without an appropriate protective equipment.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area. Stop release. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Stop leak if safe to do so. Isolate hazard area. Eliminate all ignition sources. Use ventilation/water spray/fog to disperse vapors. Prevent runoff from entering drains, sewers or waterways. Absorb and/or contain spill with inert material, then place in suitable container.

### 6.3. Methods and material for containment and cleaning up

No additional information available

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Pressurized container: Do not pierce or burn, even after use. Keep away from heat, sparks and flame.
- Precautions for safe handling : Avoid contact with skin, eyes and clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal.
- Handling temperature : < 120 °F
- Hygiene measures : Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Storage conditions : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Keep cool. Protect from sunlight. Store in a well-ventilated place. Store in a dry place.
- Incompatible products : acids. Oxidizing agents.
- Incompatible materials : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Glycol Ether EB (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
2-aminoethanol, ethanolamine (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm
ACGIH	ACGIH STEL (ppm)	6 ppm
ACGIH	Remark (ACGIH)	Eye & skin irr
propane (74-98-6)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
butane (106-97-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm

### 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Protective goggles. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Gas
- Appearance : Aerosol. clear. Liquid.
- Odor : Butyl
- Odor threshold : No data available
- pH : 12 - 13
- Melting point : No data available

# Baseboard Stripper

## Safety Data Sheet

Freezing point	: No data available
Boiling point	: No data available
Flash point	: (liquid portion)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: 19 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

#### 10.4. Conditions to avoid

Heat. Open flame. Sparks. Welding.

#### 10.5. Incompatible materials

acids. Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Glycol Ether EB (111-76-2)</b>	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	1300.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h
<b>2-aminoethanol, ethanolamine (141-43-5)</b>	
LD50 oral rat	1720 mg/kg female
LD50 dermal rabbit	1000 mg/kg
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.  
pH: 12 - 13

# Baseboard Stripper

## Safety Data Sheet

Serious eye damage/irritation : Not classified  
pH: 12 - 13

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

### Glycol Ether EB (111-76-2)

IARC group	3 - Not Classifiable
------------	----------------------

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified.

### Glycol Ether EB (111-76-2)

LOAEL (oral,rat,90 days)	69 mg/kg bodyweight/day Target organ: liver
NOAEL (dermal,rat/rabbit,90 days)	150 mg/kg bodyweight/day

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Harmful if swallowed. Burns to the gastric/intestinal mucosa. Gastrointestinal complaints.

Likely routes of exposure : Skin and eyes contact.;Inhalation

## SECTION 12: Ecological information

### 12.1. Toxicity

Glycol Ether EB (111-76-2)

LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container to comply with local/regional/national/international regulations.

## SECTION 14: Transport information

### Department of Transportation (DOT)

Transport document description : UN1950 Aerosols (non-flammable, (each not exceeding 1 L capacity)), 2.2

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols  
non-flammable, (each not exceeding 1 L capacity)

Transport hazard class(es) (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) :

# Baseboard Stripper

## Safety Data Sheet

DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A
DOT Vessel Stowage Other	: 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

### Additional information

Other information : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306.

### ADR

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Glycol Ether EB	CAS No 111-76-2	1 - 5
propane (74-98-6)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		
butane (106-97-8)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		

California Proposition 65 - This product does not contain trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

## SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H290	May be corrosive to metals
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways

# Baseboard Stripper


## Safety Data Sheet

H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*